



SpeedMax™ XL

14-Tooth RSN — .404 Harvester Guide Bars

BIGGER. STRONGER. LONGER-LASTING.



When you're on the toughest harvesting jobs, you want productive tools that can tackle the workload and reduce downtime. SpeedMax XL guide bars with Replaceable Sprocket Noses (RSN) from Oregon® are built to go the distance. With wide-steel bodies, SpeedMax XL guide bars are designed for improved chain retention—keeping you in the cab and on the job longer.

- + Tough, long-lasting, and durable with a retooled 14-tooth replaceable sprocket nose and industrial grade components.
- + Stronger & wider bar body.
- + An extended-length sprocket nose completely covers normal areas of accelerated rail wear and can be replaced several times—increasing the life of the bar body.
- + Fits the most popular harvesting equipment.



SMR14T

SpeedMax™ XL Guide Bar

Strength is performance. The SpeedMax XL is a stronger, stiffer solid harvester guide bar. Get more uptime with more efficient cutting.

WIDER

The SpeedMax XL wider design throws less chain and is built for high output.

STRONGER

The SpeedMax XL flexes less because of its wider design and the chrome-moly steel it's made from.

LUBRITEC™

Keeps your chain and guide bar oiled, for less friction and longer life.

Replaceable Sprocket Nose

A re-engineered nose provides exceptional durability and reliability on the job.

14-TOOTH NOSE

The larger 14-tooth sprocket requires fewer rotations, which reduces heat build-up and extends the life of the nose.

INDUSTRIAL STRENGTH BEARINGS

Our industrial high-alloy bearings are 14% thicker than the competition.

EXTENDED LENGTH

With an extended nose-length - now 5.5", previously 4" - the replaceable sprocket nose absorbs most rail wear and can be replaced several times. The guide bar bodies last longer as a result.

Q

11–13 Tooth drive sprockets

542SMRQ104 752SMRQ114
 592SMRQ104 752SMRQ149
 602SMRQ163 802SMRQ104
 642SMRQ003 802SMRQ114
 642SMRQ104 822SMRQ149
 642SMRQ114 902SMRQ114
 672SMRQ163 902SMRQ149
 752SMRQ003 002SMRQ114
 752SMRQ104

R

14–16 Tooth drive sprockets

642SMRR104
 752SMRR149
 752SMRR104
 752SMRR114
 802SMRR114
 822SMRR149

S

17–19 Tooth drive sprockets

602SMRS163
 672SMRS163
 752SMRS149
 822SMRS149
 902SMRS149



.404"



.080"



54 to 100 cm

